




NIXALITE
1025 16TH AVE
EAST MOLINE, IL 61244
TOLL FREE: 1-888-624-1189
PHONE: (309) 755-8771
FAX: (309) 755-0077
www.nixalite.com



SOLATRIM™ - PANEL FRONT

SOLATRIM™ - PANEL BACK

SOLATRIM PANEL SPECIFICATIONS:

CONSTRUCTION: EACH PANEL IS MADE FROM CORROSION RESISTANT 3003-H14 ALUMINUM, 0.025" (0.63MM) THICK (22 GA.)

PEEL-AND-STICK TAPE: 3M ACRYLIC FOAM TAPE ON BACK OF PANEL

DIMENSIONS: EACH SOLATRIM PANEL IS 48" LONG, 6-3/4" HIGH, 0.025" THICK (122 CM LONG, 17.1 CM HIGH AND 0.63 MM THICK)

WEIGHT: 11 OUNCES (0.68 POUNDS OR 0.3 KG) PER PANEL

COATING (FRONT): BLACK POLYESTER COATING

COATING (BACK): WHITE POLYESTER PRIMER COATING

FOR 3-PART SPECIFICATIONS OR IF YOU HAVE ANY QUESTIONS ABOUT THE SOLATRIM BARRIERS, CONTACT NIXALITE OF AMERICA INC.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 3985-017.

